



## SPECIFICATIONS

### Control Unit Models:

9450 Model 70 (NFPA-101)  
9450 Model 71 (ICC compliant)

### Dimensions:

6.5" H x 4.5" W x 1.5" D  
(16.51 x 11.43 x 3.81 cm)

**Weight:** 1.5 Lbs (0.68 Kg)

**Enclosure:** White painted surface mount steel enclosure or galvanized steel flush mount enclosure

**Power:** 14-16 V AC or DC, 400mA per unit required

**Inputs:** Staff/Visitor Bypass Input  
Tamper switch DuoLink Exit Alarm Receivers Door position switch  
Door ajar input from CodeLock™

**Outputs:** 4 sets of supervised Normally Open and Normally Closed relay contacts can be used to activate staff alert panels and other auxillary devices

**Communication:** RS-485 data signaling

**Certifications:** UL Std. 294, FCC Part 15

### DuoLink Exit Alarm Receivers

### Dimensions:

12.2" L x 1.77" W x 1.30" D  
(31 x 4.5 x 3.3 cm)  
includes 30 foot (9.1 meters) cords

**Weight:** 5.75 ounces (163 grams)

**Range:** Adjustable up to 8' (2.4m) each



RF TECHNOLOGIES™

## Restraint-Free Monitoring of Residents at Risk

Code Alert provides reliable, restraint-free monitoring of residents at risk for elopement with our Wandering Management Solutions. Using radio frequency technology, this system uses lightweight transmitters worn by residents, receivers to detect a resident's presence, reed switches to know when the door is open and a control unit that issues the alarm. This system can be reset and bypassed at the monitored location using the control unit keypad, allowing staff and visitors the ability to move about the facility without barriers, while helping to keep residents safe.

## Easy to Use System

Residents can wear the transmitter on their wrist, ankle, or attached to wheelchairs. The transmitter is secured with a durable band and is protected with a water-tight case. Long lasting 1.5-year and 3-year battery life transmitters reduce operating costs and eliminate the need to frequently order replacements. In the event a resident enters a monitored area while the door is open, an alarm will sound locally as well as at optional remote locations.

## Customizable Safety features

The Code Alert Wandering Management Solution includes innovative features that ensure the well being of residents. Our Visitor Bypass feature alarms when a monitored resident follows a visitor or staff member through a monitored area. Supervised wiring and tamper switches notify you if damage, vandalism or power outages occur. The ability for authorized personnel to control and customize settings through the control unit keypad allows features to be changed quickly and easily.

## Model 70 Options

- **Transmitter Tester** -Portable tester carried by staff to document that worn transmitters are functioning
- **Staff Alert Panel** -Remote annunciator monitors up to 8 exits, usually placed at nurse station
- **Programmable Timer** - Automatically switches system from wandering management to perimeter alarm system for increased security during off-hours
- **CodeLock Electromagnetic Lock** - Automatically secures door when resident with transmitter enters monitored area
- **Automatic Door/Elevator Deactivation Module** - Can deactivate a motorized sliding door, or hold an elevator door open preventing wandering residents from leaving the floor

3125 North 126th Street, Brookfield, WI 53005 USA  
phone: 800.669.9946 web: [www.rft.com](http://www.rft.com)